



PRODUCTS:

LARGE DIAMETER SEAMLESS PIPE: (MADE IN CANADA)

Size range: 16" through 30"

Specifications: A/SA106B/C/NACE
A/SA106B/C

Schedules: STD/XHVY/TRU40/TRU80

SEAMLESS PIPE:

Size range: 1/4" through 30"

Specifications: S/A106B/C/API5LBX42

Schedules: through XXHVY

LOW TEMP PIPE:

Size range: 1/4" through 16"

Specifications: S/A333-6

Schedules: STD/XHVY/SCH160/XXVHY

WELDED PIPE:

Size range: 2" through 48"

Schedules: SCH20/STD/XHVY

Specification: S/A53-B/API5LX42

STOCK LOCATIONS:

511 W. Armory DR. • STE B

South Holland • IL 60473

P: 708.566.5778

F: 708.893.0018

11011 Sheldon RD.

Houston, TX 77044

P: 708.566.5778

F: 708.893.0018

SERVICES:

PRODUCTION SAW CUTTING:
cut to length/precision tolerances

BEVELING:
Machine and torch beveling

CLEAN AND CAPPED:
I.D. and O.D. cleaning for ammonia/
oxygen service

COATINGS:
All exterior and interior coatings
FBE, TGF-3, I.D. Jet fuel linings

GROOVING:
Roll grooving diameters 2" through 16"

LOGISTICS:
We can provide delivered pricing anywhere in
the Continental US and Canada



STANDARD CHART

STEEL PIPE SIZES, WEIGHTS, DIMENSIONS



Size	Outer Diameter	Schedule 5	Schedule 10	Schedule 20	Schedule 30	Schedule 40	Standard	Schedule 60	Schedule 80	X-Heavy	Schedule 100	Schedule 120	Schedule 140	Schedule 160	XX-Heavy
1/8	0.405	.035 .138	.049 .1863			.068 2.447	.068 2.447		.095 .3145	.095 .3145					
1/4	0.540	.049 .2570	.065 .3297			.088 .4248	.088 .4248		.119 .5351	.119 .5351					
3/8	0.675	.049 .3276	.065 .4235			.091 .5676	.091 .5676		.126 .7388	.126 .7388					
1/2	0.840	.065 .5383	.083 .6710			.109 .8510	.109 .8510		.147 1.088	.147 1.088				.187 1.304	.294 1.714
3/4	1.050	.065 .6838	.083 .8572			.113 1.131	.113 1.131		.154 1.474	.154 1.474				.218 1.937	.308 2.441
1	1.315	.065 .8678	.190 1.404			.133 1.679	.133 1.679		.179 2.172	.179 2.172				.250 2.844	.358 3.659
1-1/4	1.660	.065 1.107	.109 1.806			.140 2.273	.140 2.273		.191 2.997	.191 2.997				.250 3.765	.382 5.214
1-1/2	1.900	.065 1.274	.109 2.638			.145 2.718	.145 2.718		.200 3.631	.200 3.631				.281 4.859	.400 6.408
2	2.375	.065 1.604	.109 2.638			.154 3.653	.154 3.653		.218 5.022	.218 5.022				.343 7.444	.436 9.029
2-1/2	2.875	.083 2.475	.120 3.531			.203 5.793	.203 5.793		.276 7.661	.276 7.661				.375 10.01	.552 13.70
3	3.500	.083 3.029	.120 4.322			.216 7.576	.216 7.576		.300 10.25	.300 10.25				.437 14.32	.600 18.58
3-1/2	4.00	.083 3.472	.120 4.973			.226 9.109	.226 9.109		.318 12.51	.318 12.51					.636 22.85
4	4.500	.083 3.915	.120 5.613			.237 10.79	.237 10.79	.281 12.66	.337 14.98	.337 14.98		.437 19.01		.531 22.51	.674 27.54
4-1/2	5.00					.247 12.53			.355 17.61						.710 32.53
5	5.563	.109 6.349	.134 7.770			.258 14.62	.258 14.62		.375 20.78	.375 20.78		.500 27.04		.625 32.96	.750 38.55
6	6.625	.109 7.585	.134 9.289			.280 18.97	.280 18.97		.432 28.57	.432 28.57		.562 36.39		.718 45.30	.864 53.16
7	7.625					.301 23.57			.500 38.05						.875 63.08
8	8.625	.109 9.914	.148 13.40	.250 22.36	.277 24.70	.322 28.55	.322 28.55	.406 35.64	.500 43.39	.500 43.39	.593 50.87	.718 60.63	.812 67.76	.906 74.69	.875 72.42
9	9.625					.342 33.90			.500 48.72						
10	10.750	.14 15.19	.165 18.65	.250 28.04	.307 34.24	.365 40.48	.365 40.48	.500 54.74	.593 64.33	.500 54.74	.718 76.93	.843 89.20	1.000 104.1	1.125 115.7	
11	11.750					.375 45.55			.500 60.07						
12	12.750	.156 21.07	.180 24.20	.250 33.38	.330 43.77	.406 53.53	.375 49.56	.562 73.16	.687 88.51	.500 65.42	.843 107.2	1.000 125.5	1.125 139.7	1.312 160.3	
14	14.000	.156 23.06	.250 36.71	.312 45.68	.375 54.57	.437 63.37	.375 54.57	.593 84.91	.750 106.1	.500 72.09	.937 130.7	1.093 150.7	1.250 170.2	1.406 189.1	
16	16.000	.165 27.90	.250 42.05	.312 52.36	.375 62.58	.500 82.77	.375 62.58	.656 107.5	.843 136.5	.500 82.77	1.031 164.8	1.218 192.3	1.437 223.5	1.593 245.1	
18	18.000	.165 31.43	.250 47.39	.312 59.03	.437 82.06	.562 104.8	.375 70.59	.750 138.2	.937 170.8	.500 93.45	1.156 208.0	1.375 244.1	1.562 274.2	1.781 308.5	
20	20.000	.188 39.78	.250 52.73	.375 78.60	.500 104.1	.593 122.9	.375 78.60	.812 166.4	1.031 209.9	.500 104.1	1.280 256.1	1.500 296.4	1.750 341.1	1.968 379.0	
24	24.000	.218 55.37	.250 63.41	.375 94.62	.562 140.8	.687 171.2	.375 94.62	.968 238.1	1.218 296.4	.500 125.5	1.531 367.1	1.812 429.4	2.062 483.1	2.343 541.9	
26	26.000		.312 85.60	.500 136.2			.375 102.6		.500 136.2						
28	28.000		.312 92.26	.500 146.8	.625 182.7		.375 110.6		.500 146.8						
30	30.000	.250 79.43	.312 98.93	.500 157.5	.625 196.1		.375 118.6		.500 157.5						
32	32.000		.312 105.6	.500 168.2	.625 20.94	.688 230.1	.375 126.7		.500 168.2						
34	34.000		.344 123.7	.500 178.9	.625 222.8	.688 244.8	.375 134.7		.500 178.9						
36	36.000		.312 118.9	.500 189.6	.625 236.1	.750 282.3	.375 142.7		.500 189.6						
42	42.000						.375 166.7		.500 221.6						
48	48.000						.375 190.7		.500 253.6						

Browse the standard pipe chart to select the pipe dimensions and weights that meet your requirements